



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/775,633	02/10/2004	Kevin Burak	226432	1325

23460 7590 07/12/2007  
LEYDIG VOIT & MAYER, LTD  
TWO PRUDENTIAL PLAZA, SUITE 4900  
180 NORTH STETSON AVENUE  
CHICAGO, IL 60601-6731

EXAMINER
----------

LAI, ANDREW

ART UNIT	PAPER NUMBER
----------	--------------

2616

MAIL DATE	DELIVERY MODE
-----------	---------------

07/12/2007

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

## Office Action Summary

Application No.

10/775,633

Applicant(s)

BURAK, KEVIN

Examiner

Andrew Lai

Art Unit

2616

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 10 February 2004.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-19 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-19 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 10 February 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO/SB/08)  
Paper No(s)/Mail Date 7/31/06.
- 4) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_.
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_.

## DETAILED ACTION

### ***Claim Rejections - 35 USC § 102***

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

2. Claims 1, 2, 3, 4 – 7 and 13 are rejected under 35 U.S.C. 102(e) as being anticipated by Okada (US 2002/0018442).

Okada discloses “a LAN path control system capable of easily changing active port of terminals” (Abstract lines 1-3) comprising the following features:

#### **Regarding independent claims 1, 2 and 3**

**Examiner's note:** Okada's system (fig. 3) has a plurality of terminals (fig. 3 items 301-312) each having “a main controller and two LAN controllers which have LAN communication ports (not shown) respectively” ([0050] lines 1-3 and also shown in fig. 3, e.g., “terminal 301” having “main cont. 321” and “LAN cont.0 322” and “LAN cont.1 323”). It is important to note that Okada's teachings on “LAN controllers” are equivalent to “communication ports” since each LAN controller is directly coupled to a respective communication port as said hereinabove. For example, [0055] lines 6-8 recite “First and second MAC address areas are for registering the specific MAC addresses assigned to

Art Unit: 2616

the LAN controllers 322 and 323 respectively". It should be understood as specific MAC addresses assigned to the communication ports each LAN controller has, respectively. For another example, [0051] recites "*each of the LAN controllers is assigned with a specific media access control (MAC) address*". It should be understood as each associated port being assigned a MAC address.

With above background information, below is a discussion of said claims.

**Claim 1**, *an industrial network redundancy system* (see "a local area network path controlling system" recited [0013] line 2) *for providing communication redundancy between industrial network nodes* (see "which is capable of easy changing an active port of a terminal" recited [0013 lines 2-3) *comprising:*

*at least two industrial network nodes* (refer to fig. 3 and see "each of the terminals 301-312" recited [0050] line 1), *each having a plurality of network ports* (see "a terminal which is used in a local area network and capable of easy changing from an active port to a standby port thereof" recited [0014] lines 1-4) *to a switched network* (fig. 3 see the middle section for "0 transmission line" in block 361 and "1 transmission line" in block 362, each having various "HUB", and see "plurality of hubs forming a simplex basic local area network" recited [0017] line 4);

*a plurality of communication paths* (fig. 3 depicting a plurality of paths between, e.g. terminal 301 and terminal 307 and see "it is therefore an object of this invention to provide a local area network path controlling system" recited [0013] lines 1-2) *between respective network ports of the at least two industrial nodes* (fig. 3 depicting two ports each terminal 301-312 and each port having its respective path, and fig. 4 showing

Art Unit: 2616

detailed structure of a terminal having "LAN. CONT.0 [LAN controller 0] 322" associated with a port and "LAN.CONT.1 323" with another port), *wherein the plurality of communication paths comprises the switched network* (fig. 3 noting that said paths connecting to said "HUBs" in "0/1 transmission line" blocks "forming a simplex basic local area network" recited [0017] line 4); *and*

*a respective data link protocol layer residing on each of the at least two industrial network nodes* (see "each of the terminals has first and second local area network controllers and assigned with specific internet protocol address" recited [0017] lines 5-7) *for determining which of the plurality of communication paths to utilize for outgoing communications* (**1:** refer to fig. 4 showing a "CPU 401" and see "CPU401 to control the whole of the terminal 301. The [a] program makes the CPU 401 serve as an equipment illustrated in fig. 7" recited [0057] lines 2-4. **2:** refer to fig. 7 and see "A first failure detecting portion 704 detects a link failure between the active controller 322 and the hub connected to the active controller. A changing porting 705 changes the active controller from the LAN controller 322 to the LAN controller 323" recited [0058] lines 14-19) *and for determining to which port of the other of the at least two industrial network nodes such communications should be addressed* (see "when the CPU 401 receives the normal reply, it abstracts the source IP address and the source MAC address from the received normal reply" recited [0070] lines 1-3 and "Thus the terminal 301 has the specific IP addresses and the MAC addresses of the other terminals which are put in operation in the destination information table 412. The terminal 301 can communicate with the other terminals by the use of the specific IP addresses and the MAC addresses

registered in the destination information table 412” recited [0071] lines 1-3. Also refer to fig. 4 to see said “destination information table 412” as well as a “own terminal information table 413”).

**Claim 2**, *an industrial network redundancy system* (see “a local area network path controlling system” recited [0013] line 2) *for providing communication redundancy* (see “which is capable of easy changing an active port of a terminal” recited [0013] lines 2-3) *between a first industrial network node* (see fig. 3, e.g. “terminal 301”) *and a plurality of second industrial network nodes* (see fig. 3, e.g. “terminal 302-312”) *comprising:*

*the first industrial network node* (fig. 3 e.g. “terminal 301”) *and the plurality of second industrial network nodes* (fig. 3, e.g. “terminal 302-312”), *each having a plurality of network ports* (see “a terminal which is used in a local area network and capable of easy changing from an active port to a standby port thereof” recited [0014] lines 1-4) *to a switched network* (fig. 3 see the middle section for “0 transmission line” in block 361 and “1 transmission line” in block 362, each having various “HUB”, and see “plurality of hubs forming a simplex basic local area network” recited [0017] line 4);

*a plurality of communication paths* (fig. 3 depicting a plurality of paths between, e.g. terminal 301 and all other terminals 302-312 and see “it is therefore an object of this invention to provide a local area network path controlling system” recited [0013] lines 1-2) *between respective network ports of the first industrial node and each of the plurality of second industrial network nodes* (fig. 3 depicting two ports each terminal 301-312 and each port having its respective path, and fig. 4 showing detailed structure

Art Unit: 2616

of a terminal having "LAN. CONT.0 [LAN controller 0] 322" associated with a port and "LAN.CONT.1 323" with another port), *all of the plurality of communication paths comprising the switched network* (fig. 3 noting that said paths connecting to said "HUBs" in "0/1 transmission line" blocks "forming a simplex basic local area network" recited [0017] line 4); *and*

*a respective data link protocol layer residing on the first industrial network node and each of the plurality of second industrial network nodes* (see "each of the terminals has first and second local area network controllers and assigned with specific internet protocol address" recited [0017] lines 5-7) *wherein the plurality of communication paths are switched base on detection of a fault in connectivity between nodes* (**1:** refer to fig. 4 showing a "CPU 401" and see "CPU401 to control the whole of the terminal 301. The [a] program makes the CPU 401 serve as an equipment illustrated in fig. 7" recited [0057] lines 2-4. **2:** refer to fig. 7 and see "A first failure detecting portion 704 detects a link failure between the active controller 322 and the hub connected to the active controller. A changing porting 705 changes the active controller from the LAN controller 322 to the LAN controller 323" recited [0058] lines 14-19) *and for determining to which port of the other of the at least two industrial network nodes such communications should be addressed* (see "when the CPU 401 receives the normal reply, it abstracts the source IP address and the source MAC address from the received normal reply" recited [0070] lines 1-3 and "Thus the terminal 301 has the specific IP addresses and the MAC addresses of the other terminals which are put in operation in the destination information table 412. The terminal 301 can communicate with the other terminals by

the use of the specific IP addresses and the MAC addresses registered in the destination information table 412" recited [0071] lines 1-3. Also refer to fig. 4 to see said "destination information table 412" as well as a "own terminal information table 413").

**Claim 3**, *an industrial network node* (see "it is another object of this invention to provide a terminal" recited [0014] lines 1-2) *comprising:*

*a plurality of network ports* (see "a terminal which is used in a local area network and capable of easy changing from an active port to a standby port thereof" recited [0014] lines 2-4) *connected to a single switched network* (see fig. 3, e.g. "terminal 301" with "LAN cont. 0 322" [port 0] and "LAN cont.1 323" [port 1] both connected to a "plurality of hubs forming a simplex basic local area network" recited [0017] line 4), *wherein a second industrial network node* (fig. 3 see, e.g. "terminal 307") *is also connected to the switched network* (fig. 3 showing "terminal 307" connected to the same network "terminal 301" connected to); *and*

*a data link protocol layer transparently usable by higher layers of a protocol stack* (see fig. 5 depicting higher layer protocol stacks, e.g. "terminal IP address" "CH IP address" on top of lower data link protocol layer protocol "MAC address (LAN cont.0)" and "MAC address (LAN cont.1)") *to facilitate network communications to the second industrial network node* (see "Each of the terminals is assigned with a specific internet protocol (IP) address. Furthermore, each of the LAN controllers is assigned with a specific media access control (MAC) address. In other words, each terminal has one of the specific IP address and two of the MAC addresses" recited [0051]), *the data link protocol layer being adapted to determine which of the plurality of network ports to use*



Art Unit: 2616

*to transmit a communication to the second industrial network node (1: refer to fig. 4 showing a "CPU 401" and see "CPU401 to control the whole of the terminal 301. The [a] program makes the CPU 401 serve as an equipment illustrated in fig. 7" recited [0057] lines 2-4. 2: refer to fig. 7 and see "A first failure detecting portion 704 detects a link failure between the active controller 322 and the hub connected to the active controller. A changing porting 705 changes the active controller from the LAN controller 322 to the LAN controller 323" recited [0058] lines 14-19), and to forward communication received on any of the plurality of network ports (see "when the CPU 401 receives the normal reply, it abstracts the source IP address and the source MAC address from the received normal reply" recited [0070] lines 1-3 and "Thus the terminal 301 has the specific IP addresses and the MAC addresses of the other terminals which are put in operation in the destination information table 412. The terminal 301 can communicate with the other terminals by the use of the specific IP addresses and the MAC addresses registered in the destination information table 412" recited [0071] lines 1-3. Also refer to fig. 4 to see said "destination information table 412" as well as a "own terminal information table 413").*

**Claims 4 and 5**, *each industrial network node comprises a communication end-station (claim 4) and the communication end-station is selected from the group consisting of a computer, a field module, and a control module (claim 5) (refer to fig. 3 and see "Each of the terminals 301-312 has a main controller and two LAN controllers." recited [0050] line 1).*

**Claim 6**, wherein the higher protocol stack layers above the data link layer include an IP layer (see “each terminal has one of the specific IP address and two of the MAC addresses” recited [0051] line 4-5 on page 5 left col., and see also fig. 5 depicting higher layer protocol stacks, e.g. “terminal IP address” “CH IP address” on top of lower data link protocol layer protocol “MAC address (LAN cont.0)” and “MAC address (LAN cont.1)”).

**Claim 7**, wherein the higher protocol stack layers above the data link layer include an application layer (it is well known in the art that networks are constructed for practical uses wherein each and every node is set to perform certain applications or functions for which application layer has to be added on top of all other layers; or otherwise the network will be idling. For teachings of network application layer, see, for example, Fred Halsall, “Computer Networking and the Internet”, Fifth Edition, ISBN 0-321-26358-8, p83 “1.5 Protocol stacks” and p84 figure 1.38 (b) depicting “Application layer protocol(s)” on top of “Network protocol IP” and “Link layer protocol”)

**Claim 9**, determining which of the plurality of network ports to use to transmit a communication to the second industrial network node, the data link protocol layer employs an alternate port based on physical link status information received from its ports and end-to-end connectivity status received (refer to fig. 7 and see “a second failure detecting portion 708 transmits a local area network check signal from a standby controller to the active controller **through the simplex based local area network** to detect a failure between two hubs 351 and 353” recited [0058] lines 29-33).

(Note: Okada does not disclose that said status received *from a reliable Logical Link Control (LLC) Type 2 or 3*, which will be discussed further below).

**Claim 13**, *transmitting a broadcast packet from the first node via the alternate port to inform network switches of the MAC address of the alternate port* (see "a first broadcasting portion is for broadcasting an address notification formed on the basis of registrations of the first table onto the simplex basic local area network when starting is carried out" recited [0018] lines 6-9, and further see fig. 5, showing "a format of an own terminal information table" recited [0025] lines 1-2, wherein shown are "MAC address (LAN CONT.0)" [active port] and "MAC address (LAN CONT.1)" [standby port]).

### ***Claim Rejections - 35 USC § 103***

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

4. Claims 11, 12, 14, 16 –18 are rejected under 35 U.S.C. 103(a) as being unpatentable over a first embodiment of Okada (US 2002/0018422) in view of a second embodiment of Okada.

Okada discloses, in a first embodiment, "a local area network (LAN) path control system according a preferred embodiment" ([0047] lines 2-3) comprising the following features:

**Regarding independent claim 11, a method of providing network communication redundancy between a first and second node** (see "It is still another object of this invention to provide a method of controlling a local area network path which is capable of way changing an active port of a terminal" recited [0015]), *the first and second node* (fig. 3, e.g. "terminal 301" as a *first node* and "terminal 307" as a *second node*) *each having at least two physical network ports* (see "Each of the terminals 301-312 has a main controller and two LAN controllers which have LAN communication ports (not shown) respectively" recited [0050] lines 1-3, and also shown in fig. 3, e.g., "terminal 301" having "main cont. 321" and "LAN cont.0 322" and "LAN cont.1 323"), *wherein for each node, one physical port is a primary port* (see "Either of the first local area network controller or the second local area network controller is put in service and serves as an active controller" recited [0017] lines 12-14) *associate with a primary communications stack and the other physical port is an alternate port* (see "The first specific media access control address is used for an active media access control address when the first local area network controller is the active controller" recited [0017] lines 14-17) *and the other physical port is an alternate port* (refer to fig. 3 and see "the LAN controller 323 is the standby controller when the LAN controller 322 is the active controller" recited [0058], starting first line on p5 left col., lines 33-35 on the right col.), *the method comprising:*

*determining at the first node that a communication fault has occurred on that node's primary port* (refer to fig. 7, depicting a program that "makes the CPU 401 serve as an equipment" recited [0057] lines 3-4 and "for the CPU 401 to control the while of

Art Unit: 2616

the terminal 301" recited [0057] lines 2-3 wherein "CPU 401" is depicted in fig. 4 running "terminal 301", and see "a first failure detecting porting 704 detects a link failure between the active controller 322 [see fig. 4] and the hub connected to the active controller" recited [0058] lines 14-19 on p5 right col.);

*forwarding further outgoing network communications associated with the primary communications stack from the alternate port of the first node (refer to fig. 7 and see "a changing portion 705 changes the active controller from the LAN controller 322 to the LAN controller 323 (or the LAN controller 323 to the LAN controller 322) [depending which is the original active controller]" recited [0058] 17-20 on p5 right col.)*

Said first embodiment of Okada does not expressly disclose (although it would have been an obvious feature of the first embodiment) the following features:

*unbinding the primary communications stack from the primary port at the first node transparently to communications stack layers above a data link layer;*

*binding the primary communications stack to the alternate port at the first node transparently to communications stack layers above the data link layer.*

Okada also discloses, in a second embodiment, "another related LAN path control system" ([0047] lines 2-3) wherein (see fig. 2) "the host computer 210 is connected to both of the communications adapters 230 and 232 while the host computer 220 is connected to the communications adapters 240. Both of the communications adapters 230 and 232 are connected to the communications adapter 240 through a network 250" ([0037] lines 3-8) and "the host computers 210 and 220 are assigned with IP addresses IP=A and IP=B, respectively. The communications adapters

230, 232 and 240 are assigned with MAC addresses MAC=a, MAC=c and MAC=b, respectively" ([0038]) comprising the following features:

*unbinding the primary communications stack from the primary port at the first node transparently to communications stack layers above a data link layer;*

*binding the primary communications stack to the alternate port at the first node transparently to communications stack layers above the data link layer.*

(see "when the failure of the communication adapter 230 is detected, the host computer 210 decides to assign the work of the communications adapter 230 to the communications adapter 232. Then the host computer commands the communication adapter 232 to operate" recited [0040])

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system in the first embodiment of Okada by adding the features of the second embodiment of Okada to the first embodiment in order to provide a smoother operation node which minimizes data loss. Note that this feature, to one skilled in the art, should have been in fact implied even in the first embodiment of Okada even though Okada has no express teaching therein.

**Regarding dependent claims**

Okada's first embodiment discloses the following features:

**Claim 12**, *wherein each physical network port of the first node has a distinct network and MAC address within the switched network* (see "furthermore, each of the LAN controller is assigned with a specific media access control (MAC) address" recited [0051] line 2 on p4 right col. line 3 on p5 left col. line 1)

**Claim 14**, wherein the primary port and alternate port of the first node are connected to the switched network via different network switches (see “The first local area network controller is directly connected to one of the hubs ... The second local area network controller is directly connected to another one of the hubs” recited [0017 lines 8-12).

**Claim 16**, wherein the first and second nodes are each of a type selected from the group consisting of a computer, a field module, and a control module (see “Each of the **terminals** 301-312 has a main **controller** and two LAN **controllers**.” recited [0050] line 1).

**Claim 17**, wherein the communications stack layers above the data link layer include an IP layer (see “each terminal has one of the specific IP address and two of the MAC addresses” recited [0051] line 4-5 on page 5 left col., and see also fig. 5 depicting higher layer protocol stacks, e.g. “terminal IP address” “CH IP address” on top of lower data link protocol layer protocol “MAC address (LAN cont.0)” and “MAC address (LAN cont.1)”).

**Claim 18**, wherein the higher protocol stack layers above the data link layer include an application layer (it is well known in the art that networks are constructed for practical uses wherein each and every node is set to perform certain applications or functions for which application layer has to be added on top of all other layers; or otherwise the network will be idling. For teachings of network application layer, see, for example, Fred Halsall, “Computer Networking and the Internet”, Fifth Edition, ISBN 0-

Art Unit: 2616

321-26358-8, p83 "1.5 Protocol stacks" and p84 figure 1.38 (b) depicting "Application layer protocol(s)" on top of "Network protocol IP" and "Link layer protocol").

5. Claims 8, 10, 15 and 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Okada (US 2002/0018422) in view of Kalkunte et al (US 2002/0010791, Kalkunte hereinafter)

Okada discloses claimed limitations in paragraphs 2 and 4 above. Okada does not disclose the following features:

**Claims 8 and 19**, wherein the switched network further comprises at least one IEEE 802.1d compliant bridge.

**Claims 10 and 15**, wherein the plurality of network ports conform to an IEEE 802.3 aggregation standard.

Kalkunte discloses "trunking and mirroring across stacked gigabit switches" (p1 left col. lines 1-2) comprising the following features:

**Claims 8 and 19**, wherein the switched network further comprises at least one IEEE 802.1d compliant bridge (see "When the packet comes in from the ingress port the decision to accept the frame for learning and forwarding is done based on several ingress rules. These ingress rules are based on the Protocols and Filtering Mechanisms supported in the switch. The protocols which decide these rules are 802.1d (Spanning Tree Protocol), 802.1p and 802.1q" recited [0091] line 1, left col., to line 6, right col.).

**Claims 10 and 15**, wherein the plurality of network ports conform to an IEEE 802.3 aggregation standard (see "Check if the packet is an IP packet (check for



Art Unit: 2616

Ethernet V2 type, 802.3, tagged Ethernet V2 and Tagged 802.3 types of Packets)" recited [0210] lines 1-3).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system and method of Okada by adding the Ethernet 802.1d and 802.3 features used by Kalkunte to Okada in order to provide faster and more efficient system wherein "bridges [can] typically utilize what is known as the 'spanning tree' algorithm to eliminate potential data loops" as pointed out by Kalkunte ([0008] lines 13-15).

6. Claims 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over Okada (US 2002/0018422) in view of Dreyer et al (US 6,098,103, Dreyer hereinafter)

Okada discloses claimed limitations in paragraphs 2 and 4 above. Okada does not disclose the following features:

**Claim 9**, connectivity status received *from a reliable Logical Link Control (LLC) Type 2 or 3*.

Dreyer discloses "automatic MAC control frame generating apparatus for LAN flow control" (col. 1 lines 1-3) comprising the following features:

**Claim 9**, connectivity status received *from a reliable Logical Link Control (LLC) Type 2 or 3* (see "MA\_DATA.request primitive is generated in accordance with IEEE 802.3x clause 2.3.1.3 by the MAC client entity whenever data shall be transferred to a peer entity or entities. This can be in response to a request from higher protocol layers

or from data generated internally to the MAC client, such as required by Type 2 LLC service" recited col. 6 lines 27-32).

It would have been obvious to one of ordinary skill in the art at the time of the invention to modify the system/method of Okada by adding LLC Type 2 feature of Dreyer to Okada in order to provide an improved flow control mechanism with "enhanced speed, throughput and interoperability over this basic flow control system while maintaining full compatibility with the IEEE standard" as pointed out by Dreyer (col. 7 lines 60-63).

### ***Conclusion***

7. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

US 2003/0208618 discloses a fast failure protection using redundant network edge ports.

US 2003/0120852 discloses multiple port allocation and configurations for different port operation modes on a host.

US 6,574,477 discloses dynamic load balancing during message processing in a wireless communication service network.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Andrew Lai whose telephone number is 571-272-9741. The examiner can normally be reached on M-F 7:30-5:00 EST, Off alternative Fridays.

Art Unit: 2616

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Kwang Yao can be reached on 571-272-3182. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

KWANG BIN YAO  
SUPERVISORY PATENT EXAMINER

AL

A handwritten signature in black ink, appearing to read 'Kwang Bin Yao', is written over the printed name and title.